



Product availability: Stock - Normally stocked in distribution facility

Price\*: 201.00 USD



### Main

Range	Multi 9
Product or Component Type	Undervoltage release
Device short name	MNs
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Control Type	Delayed
9 mm pitches	2

### Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP GFP Multi 9 C60H-DC C60H-DC
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Comb busbar and distribution block compatibility	Top YES
Height	3.25 In (82.5 mm)
Width	0.71 In (18 mm)
Depth	2.68 In (68 mm)
Net Weight	0.15 Lb(US) (0.066 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.00 in <sup>2</sup> (2.5 mm <sup>2</sup> ) AWG 14) - rigid Clamp terminal bottom) - 2 0.00 in <sup>2</sup> (1.5 mm <sup>2</sup> ) AWG 16) - rigid
Wire stripping length	0.35 In (9 mm) bottom
Tightening torque	8.85 Lbf.In (1 N.m) bottom

## Environment

Standards	EN 60947-2 EN/IEC 60947-1
Product Certifications	PCT UR UL CSA
Pollution degree	3
Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

## Ordering and shipping details

Category	00948-M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	3606480639135
Nbr. of units in pkg.	1
Package weight(Lbs)	2.68 Oz (76 g)
Returnability	Yes
Country of origin	BE

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.14 In (2.9 cm)
Package 1 width	3.15 In (8 cm)
Package 1 Length	3.70 In (9.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	23.88 Oz (677 g)
Package 2 Height	3.43 In (8.7 cm)
Package 2 width	3.94 In (10 cm)
Package 2 Length	10.43 In (26.5 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Weight	14.51 Lb(US) (6.58 kg)
Package 3 Height	11.81 In (30 cm)
Package 3 width	11.81 In (30 cm)
Package 3 Length	15.75 In (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Circularity Profile

 [End Of Life Information](#)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product Life Status : **Commercialised**